

# 3" Installation Guide

Please read the instructions before installing your burner and fireglass. If at any point you are unsure about how to install the product, or just want to make sure you are doing it right PLEASE call or email us (909) 989-6129 [Ed@Moderustic.com](mailto:Ed@Moderustic.com). Not installing properly, can delay the completion of the install, and may require you to buy more product if you need to remove any.

1. Dry-Clean your fireplace, with a wire brush, to remove surface soot build up.
  - a. NOTE: If you planning to apply a fresh coat of fireplace paint DO-NOT use any liquids to clean your fireplace - as this could cause the fireplace paint to bubble and crack. If you don't have our step by step guide on how to paint your fireplace please request one by emailing us at ([Ed@Moderustic.com](mailto:Ed@Moderustic.com)). **Importantly** - mask off the areas that you don't want any paint to get on. Also, make sure to open up your windows to allow the paint fumes to escape. Spray your paint and remove the masking.
2. Pour in your filler.
  - a. NOTE: You can apply as much filler as you like to get a fuller look without spending more on fireglass; meaning that you could pour 4" inches of filler and have 3" inch fill of fireglass for an overall height of 7" inches in your fireplace. Versus say 2" inches worth of filler and 3" inches of fireglass for a total of 5" inches worth of overall height in your fireplace.
3. Now you want to hook up your burner and place it in the center of the fireplace. Using a pipe wrench, just connect the flex hose (hand tight) to the gas line in the fireplace. The burner comes with a flex line hose which threads on to your stub/plumbing like a garden hose would.
4. Turn on the gas supply and light the burner with a safety lighter. Check to see that the burner's flames are not too far back.
  - a. NOTE: Flames that hit the back wall of the fireplace - will cause soot and will not look good with fireglass. You can turn the pipes upside down so that the holes are facing down. This will cause the flame pattern to be more erratic.
5. When using the 3" inch method, pour the first inch of glass over your filler and burner. If necessary pull the burner up through the fireglass to to reveal the surface of the burner. Test the burner flame again until you are happy with its flame height / pattern / and location.
  - a. NOTE: When doing the 3" inch method, make sure that the burner is not covered with more than 2" inches of fireglass below the top surface of the glass.
6. Now all that's left is the remaining 2 inches worth of glass to install, and your burner is positioned and working properly, it is time to pour in the rest of your glass. When pouring your base glass, start from the front and work your way to the back, pouring in slowly, or using a small garden shovel.

It's as easy as that!!! If you have any questions, please send us an email or call us direct. We are always glad to help. We want you to be happy with the look of your fireplace. Thank you again for choosing Moderustic.com.

Moderustic Inc

[www.Moderustic.com](http://www.Moderustic.com) or [www.AquaticGlassel.com](http://www.AquaticGlassel.com)

9467 9<sup>th</sup> Street #D Rancho Cucamonga, California 91730

Phone 909 989 6129 Fax 909 944 3811

Ed Jaunzemis [Ed@Moderustic.com](mailto:Ed@Moderustic.com) or [Jaunzemis@msn.com](mailto:Jaunzemis@msn.com)